

DESCRIPTION

This heavy-duty acid replacement product has the performance of hydrofluoric and sulfuric acids, but is non-corrosive to skin, making it far safer to users. It is DOT non-regulated, and no EPCRA risk management plan filing is required. Non-Phosphorus.

As an aluminum cleaner and brightener, it has outstanding calcium, limescale and silicate-deposit removal properties. It quickly removes corrosion and oxidation, leaving surfaces bright and clean. It is ideal for use on aluminum trailer bodies, boats, building materials and most other exterior aluminum surfaces.

As a coil cleaner, it removes dust, dirt, grime, grease and oxidation from aluminum or copper coils as well as fins of cooling units and air conditioners. Use it regularly to clean coils for more efficient operation and lower power consumption.

CAUTION:

May be harmful if swallowed. Wear rubber gloves and goggles when handling.

FIRST AID:

IF IN EYES: Flush eyes and under eyelids with plenty of cool water for at least 15 minutes, holding eyelids open during flushing. Obtain immediate medical attention.

IF ON SKIN: Immediately flush with soap and water. Remove contaminated clothing and launder separately before reuse. If irritation persists, obtain medical attention.

IF SWALLOWED: Do not induce vomiting. If person is conscious, give 2 glasses of water to dilute stomach contents. Contact physician or poison control center immediately. Never give anything by mouth if victim is unconscious, is rapidly losing consciousness, or is convulsing.

IF INHALED: Remove person to fresh air. If breathing has stopped administer artificial respiration. If breathing is difficult, give oxygen and obtain medical attention.

See *M.S.D.S.* for complete safety information.

KEEP OUT OF REACH OF CHILDREN

HANDLING AND STORAGE: Keep container tightly closed when not in use. Do not store in unmarked containers. Use plastic containers to mix solutions. Do not store in metal pails, drums, or sprayers. Keep away from metal powders. Avoid contact with oxidizers or reducing agents, alkalis, chlorates, nitrates. Contact with hypochlorites will liberate toxic gases. Rinse empty container before disposal.

TOTAL SOLUTIONS®

INDUSTRIAL CLEANERS
and DEGREASERS

A-R ALUMINUM & COIL CLEANER

Acid Replacement
with Acid Performance

- REPLACES HYDROFLUORIC AND SULFURIC ACIDS
- CLEANS AND BRIGHTENS CORRODED AND OXIDIZED ALUMINUM
- REMOVES DUST, GREASE, AND OXIDATION FROM COILS
- DOT NON-REGULATED
- NO RISK MANAGEMENT PLAN FILING REQUIRED

CAUTION:

May be harmful if swallowed.

See side panel for further cautions and first aid instructions.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS:

☐ 5 ☐ 6 ☐ 20 ☐ 30 ☐ 55 Gallons

Manufactured By: Total Solutions®
PO Box 240014 • Milwaukee, WI 53224

DIRECTIONS

ALWAYS TEST IN AN INCONSPICUOUS AREA BEFORE USING THIS PRODUCT.

Wear rubber gloves and goggles when handling. Use full strength for heavy duty cleaning. May be diluted with up to 5 parts water for maintenance or light cleaning and brightening. Brush, spray, or swab onto the surface to be cleaned, allow to penetrate soils, then rinse thoroughly with clean water. Use with care on painted surfaces.

Use plastic pails for diluting and dispose of excess solution immediately after use.

Do not use on anodized aluminum.

This Product Contains/CAS #: Water/7732-18-5; Organic Acid Salt/Proprietary; Organic Salt/21351-38-3; Surfactant/Proprietary.

NFPA® RATINGS
FLAMMABILITY

HEALTH  REACTIVITY

0104.121112