

DESCRIPTION

ALUMINUM TRANSMISSION & ENGINE CLEANER is a concentrated, completely soluble powder designed to function most efficiently at elevated temperatures. It cleans and strips away oil, grease and other deposits from transmissions, radiators, and other metal parts without foaming problems. It will not leave a film or residue on parts and it will not plug up spray cabinet's jets, or build-up inside the spray cabinet. ALUMINUM TRANSMISSION & ENGINE CLEANER is also safe for cleaning both aluminum and cast iron parts that are in the spray cabinet together.

DIRECTIONS FOR USE

For Use In Spray Cabinets:

Use 1 to 2 ounces of ALUMINUM TRANSMISSION & ENGINE CLEANER per gallon of tank water. Spray cabinet temperature should be maintained at 190°F. The pH level of the spray cabinet solution should be maintained at 12 to 13. If foaming becomes a problem in the spray cabinet it is usually due to the surfactants in the greases and oils that are being removed from the parts. If this happens, be sure to use the spray cabinet oil skimmer, or clean out the spray cabinet of any oily residue. A defoamer may also be used to control foaming problems. When disposing of the water be sure to adjust the pH back down close to neutral (7). The sludge at the bottom of the spray cabinet must be disposed of in a proper fashion, most likely with waste oil.

For Use As A Dipping Solution:

Dissolve 1 ounce of ALUMINUM TRANSMISSION & ENGINE CLEANER per gallon of water in dipping tank. Maintain water temperature at or above 190°F. Dip parts to be cleaned into the solution, let soak for 15 to 20 minutes, then rinse. More ALUMINUM TRANSMISSION & ENGINE CLEANER may be added for extremely soiled parts.

ALUMINUM TRANSMISSION & ENGINE CLEANER

WARNING:

HARMFUL IF SWALLOWED.

Eye irritant. See side panel for further precautions and first aid instructions.
KEEP OUT OF REACH OF CHILDREN

Sold By:

WARNING:

HARMFUL IF SWALLOWED.

Eye irritant. Avoid contact with eyes. Do not mix with any other chemical.

FIRST AID

IF SWALLOWED: Contact a physician or poison control center immediately. DO NOT induce vomiting.

IF IN EYES: Flush eyes with water for at least 15 minutes. If irritation is persistent, contact a physician.

IF ON SKIN: Wash skin with soap and water. Remove all contaminated clothing and launder separately before reuse. If irritation is persistent, contact a physician.

IF INHALED: Remove person to fresh air. If irritation is persistent, contact a physician.

See M.S.D.S. for complete safety information.


KEEP OUT OF REACH OF CHILDREN

Handling & Storage: Do not store in unmarked containers. Keep container tightly closed when not in use. Rinse thoroughly with water before recycling container.

THIS PRODUCT CONTAINS:	CAS NUMBER:
Sodium Carbonate	497-19-8
Sodium Sulfate	7757-82-6
Sodium Metasilicate	6348-92-0
Sodium Tripolyphosphate	7758-29-4
Sodium Dichloroisocyanurate	51580-86-0

0663.042009

NFPA® RATINGS
Flammability



NET CONTENTS:

- 25 LBS.
- 50 LBS.
- 100 LBS.