DESCRIPTION

This industrial strength rinsing compound has been developed specifically to cut through the dulling, white chalky residue left by ice melting chemicals. Salt residue is chemically dissolved without harming sensitive painted or finished surfaces.



RESILIENT FLOOR CARE

SALT RINSE

 NEUTRALIZES CORROSIVE FILM LEET BY ICE MELT CHEMICALS

FLOORS AND CARPETS

Ice Melt Rinse Aid

• ELIMINATES DISCOLORING OF

CAUTION

May cause eve and skin irritation. May be harmful if swallowed. Avoid contact with eves. skin and clothing. Do not take internally. Wash thoroughly after handling.

FIRST AID:

IF IN EYES: Flush eves and under evelids with water for at least 15 minutes. If discomfort persists see a physician.

IF SWALLOWED: Do not induce vomiting. Call a physician immediately.

IF ON SKIN: Wash with soap and water. Remove contaminated clothing, and launder before reuse. If irritation is persistent, contact a physician.

IF INHALED: Move person to fresh air. Call a physician if irritation persists.

See MSDS for complete safety information.

KEEP OUT OF REACH OF CHILDREN

HANDLING AND STORAGE: Keep container tightly closed when not in use. Do not store in unmarked containers. Do not mix with any cleaning chemicals. Store container in cool, dry place. Keep away from alkaline material and reactive chemicals.

KEEP OUT OF REACH OF CHILDREN

May cause eve and skin irritation. May be harmful if swallowed. See side panel for additional precautions.

NET CONTENTS: □ 5 □ 6 □ 20 □ 30 □ 55 Gallons

Manufactured By: Total Solutions™ PO Box 240014 • Milwaukee, WI 53224

DIRECTIONS

FOR DAILY DAMP MOPPING: Use 1-3 ounces per gallon of rinse water. Apply liberally to floor with a mop, allowing the solution to act for several minutes. Rinse immediately with clean water, wringing out mop frequently.

TO REMOVE HEAVY FILM FROM **EQUIPMENT:** Dilute 6 ounces per gallon of rinse water. Spray liberally over the equipment surfaces and allow to act for several minutes. Rinse with clean water.

TO ELIMINATE CARPET STAINS LEFT BY ICE MELTING RESIDUE: Use 1-3 ounces per gallon of water in carpet extraction equipment. Do not use a hot solution and do not mix this product with any other chemical.

This Product Contains/CAS Number:

Water/7732-18-5: Sulfamic Acid/5329-14-6; Poly (oxyethylene) nonyl- phenol/ 9016-45-9; Perfume/Proprietary.

> **NFPA® RATINGS FLAMMABILITY**



0710 • 021111