

MATERIAL SAFETY DATA SHEET

Total Solutions
P.O. Box 240014
Milwaukee, WI 53224



GENERAL INFORMATION NUMBER: (414) 354-6417
CHEMTREC: (800) 424-9300

REVISION DATE: February 28, 2005
DATE OF ISSUE: February 28, 2005

I - Product Identification

Boiler Complete Treat "H"

PRODUCT CODE: 0901

CHEMICAL FORMULATION: Steam boiler water treatment.

NFPA HAZARD IDENTIFICATION SYSTEM: HEALTH: 2 FLAMMABILITY: 0 REACTIVITY: 0
HAZARD RATING: 4 - Extreme; 3 - High; 2 - Moderate; 1 - Slight; 0 - Insignificant

II - Hazardous Ingredients

Values reported as TWA unless noted.

SUBSTANCE	APPROX	OSHA	ACGIH	EPA 40 CFR:			CAS #
	%	PEL	TLV	302	355	372	
Sodium sulfite	5.00-15.0	N/E	N/E	N	N	N	7757-83-7
Sodium hydroxide	1.00-10.0	2 mg/m ³	2 mg/m ³ C	Y	N	N	1310-73-2
Diethylethanolamine	< 2.00	10 ppm (skin)	2 ppm (skin)	N	N	N	100-37-8
Potassium carbonate	1.00-10.0	N/E	N/E	N	N	N	584-08-7

Key: PEL: Permissible Exposure Limit TLV: Threshold Limit Value C: Ceiling level STEL: Short Term Exposure Limit
N/A: Not Applicable N/D: Not Determined N/E: Not Established Y: Yes N: No
302: CERCLA List of Hazardous Substances and Reportable Quantities (40 CFR 302.4).
355: SARA TITLE III / List of Extremely Hazardous Substances for Emergency Planning and Notification (40 CFR 355).
372: SARA TITLE III / List of Toxic Chemicals subject to Release Reporting (Community Right to Know) (40 CFR 372).

III - Physical Data

BOILING POINT (°F): N/D SPECIFIC GRAVITY (WATER = 1): 1.16
VAPOR PRESSURE (mm Hg): N/D VOC CONTENT (% by weight): N/D
VAPOR DENSITY (AIR = 1): N/D EVAPORATION RATE (WATER = 1): N/D
SOLUBILITY IN WATER: Soluble pH: 13.00 - 14.00
APPEARANCE AND ODOR: Clear, gold colored liquid, mild odor.

IV - Fire and Explosion Hazard Data

FLASH POINT (°F): None (TEST METHOD): Closed cup
FLAMMABLE LIMITS IN AIR (VOLUME %) UPPER: N/A LOWER: N/A
EXTINGUISHING MEDIA: Water, foam, carbon dioxide, dry chemical.
SPECIAL FIRE FIGHTING PROCEDURES: Cool fire exposed containers with water fog. Firefighters should be equipped with full protective gear including self-contained breathing apparatus.
UNUSUAL FIRE AND EXPLOSION HAZARD: None

V - Reactivity Data

STABILITY: Stable

INCOMPATIBILITY: Strong acids.

CONDITIONS TO AVOID: None.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may produce oxides of carbon.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: None

VI - Health Hazard Data

ROUTES OF ENTRY **INHALATION:** X **EYE CONTACT:** X **SKIN CONTACT:** X **INGESTION:** X

INGREDIENTS THAT ARE CONSIDERED BY OSHA, NTP, IARC TO BE SUSPECTED HUMAN CARCINOGENS: None

EFFECTS OF OVEREXPOSURE

IF IN EYES: Severe irritation, redness, tearing, destruction of tissue.

IF ON SKIN: Redness, irritation, burns with prolonged or repeated exposure.

IF SWALLOWED: Gastrointestinal irritation, cramps, burns to mucous membranes. Harmful or fatal if swallowed.

IF INHALED: Severe irritation of respiratory tract, pulmonary edema, laryngeal spasms.

EMERGENCY AND FIRST AID PROCEDURES

IF IN EYES: Flush eyes and under eyelids with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention.

IF ON SKIN: Flush area with water while removing contaminated clothing. Continue flushing for at least 15 minutes. Launder clothing separately before re-use. If irritation persists, obtain medical attention.

IF SWALLOWED: Contact physician or poison control center immediately. Rinse mouth with water and give affected person 1 to 2 glasses of water. Do not induce vomiting unless instructed by a physician of poison control center. Never give anything to an unconscious person.

IF INHALED: Remove person to fresh air. If irritation persists, obtain medical attention.

VII - Spill or Leak Protection

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Ventilate area. Contain spill. Soak up spilled material with inert absorbent material and place in a properly marked closed container for proper disposal.

WASTE DISPOSAL METHOD: Consult local environmental authorities.

VIII - Special Protection Information

RESPIRATORY PROTECTION: Use with adequate ventilation. If recommended Exposure Limits are exceeded wear a NIOSH approved respirator, following manufacturer's recommendations.

VENTILATION

LOCAL: Recommended

MECHANICAL: Not required

PROTECTIVE GLOVES: Chemical resistant.

EYE PROTECTION: Safety glasses or chemical goggles.

OTHER PROTECTIVE EQUIPMENT: Protective clothing, emergency shower and eye wash station.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place away from acidic material. Keep container tightly closed when not in use. Always add this product to water, never add water to this product.

OTHER PRECAUTIONS: Keep out of reach of children.

IX - Transportation Information (ground transportation only)

DOT PROPER SHIPPING NAME: Corrosive liquid n.o.s. (sodium hydroxide)

DOT CLASS: 8

DOT ID NUMBER: UN1760

DOT PACKING GROUP: II

The shipping information listed above applies only to non-bulk (< 119 gallons) containers of this product. This product may have more than one proper shipping name depending on packaging, product properties, & mode of shipment. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may apply.

REVISION DATE: February 28, 2005

Prepared by: Technical Dept

DATE OF ISSUE: February 28, 2005

This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Total Solutions assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material such vendees or users assume all risks associated with the use of this material.