### **DESCRIPTION**

FOR INSTITUTIONAL, COMMERCIAL AND INDUSTRIAL USE

Saves production, maintenance, and repair time. Protects and preserves equipment. For use on refrigerator equipment, automobiles, work-shops. Free nuts and bolts. Lubricates locks, hinges, moving parts. Stops and retards corrosion. Stops corrosion on battery terminals.

SPECIFICALLY DESIGNED TO PENETRATE DEEP TO FREE RUSTED AND CORRODED PARTS

**CAUTIONS:** May cause liver, kidney and cardiovascular damage. Suspect cancer hazard. Contains perchloroethylene, which may cause cancer. Do not swallow. Avoid eye contact. Avoid prolonged skin contact. Avoid breathing vapors and aerosols. Use only in a well ventilated area. Do not smoke while using. Keep away from heat sources, ultraviolet light, electric arcs, sparks, flames and other sources of ignition. Decomposition products are toxic and corrosive. Do not puncture or incinerate (burn) container, even when empty. Do not expose to heat or store above 120°F. Do not place can on hot surfaces or in direct sunlight. Heat may cause can to burst violently. Intentional inhalation abuse (concentrating and inhaling vapors) may be harmful or fatal.

### FIRST AID:

INGESTION: DANGER! Aspiration Hazard. DO NOT induce vomiting. Call physician or poison control center immediately.

**EYE CONTACT:** Flush with water for at least 15 minutes. Get medical attention.

SKIN CONTACT: Wash with soap and water. If irritation develops and persists, get medical attention.

INHALATION: Move to fresh air. Get medical attention if irritation or other symptoms develop and persist.

WARNING: This product contains tetrachloroethylene, which is known to the State of California to cause cancer.

### **KEEP OUT OF REACH OF CHILDREN**

See Material Safety Data Sheet for complete safety information.

CONTAINS NO OZONE DEPLETING CHEMICALS!



SPECIALTY PRODUCTS

## **HEAVY DUTY** PENETRATING OIL

Non-Conducting Up To 45,000 Volts

• LUBRICATES

CLEANS

LOOSENS NUTS AND BOLTS

RETARDS CORROSION

PENETRATES FASTER AND FARTHER

DISPLACES MOISTURE

### This Product Contains/CAS Number: Perchloroethylene/127-18-4;

Deodorized Kerosene/64742-47-8: Oil Additives/Proprietary; Carbon Dioxide/124-38-9.

### **HMIS® RATINGS:**

**DIRECTIONS** 

needed.

Remove cap and point valve opening

toward surface to be sprayed. Hold can 4-8 inches away, push button and

spray. Apply generously to surface to

be treated. Repeat application when

HEALTH - 2, FLAMMABILITY - 2, REACTIVITY - 0, PERSONAL PROTECTION - X.

8100 • 010412



# **KEEP OUT OF REACH OF CHILDREN** DANGER:

VAPORS HARMFUL. HARMFUL OR FATAL IF SWALLOWED. EYE IRRITANT. CONTENTS UNDER PRESSURE. Read carefully other cautions on back panel.

NET WEIGHT: 20 oz. (1 lb. 4 oz.) 567 g

Distributed By: Total Solutions® PO Box 240014 • Milwaukee, WI 53224