

DESCRIPTION

This water-based, high grade, one step, multi-purpose sealer penetrates and bonds to provide exceptional protection against water, stains, dirt, grease and oil. Use on concrete, wood, unglazed stone, grout, ceramic, marble, limestone, travertine, quarry tile, flagstone, terrazzo, granite, masonry, brick, slate, and stucco surfaces.

CAUTION

May cause eye irritation. Avoid contact with eyes. Wash thoroughly after handling.

FIRST AID:

IF SWALLOWED: Contact a physician or poison control center immediately. DO NOT induce vomiting.

IF IN EYES: Flush eyes with water for at least 15 minutes. If irritation is persistent, contact a physician.

IF ON SKIN: Wash skin with soap and water. Remove all contaminated clothing and launder separately before reuse. If irritation is persistent, contact a physician.

IF INHALED: Move person to fresh air. If irritation is persistent, contact a physician.

See M.S.D.S. for complete safety information.

KEEP OUT OF REACH OF CHILDREN

HANDLING AND STORAGE: Keep container tightly closed when not in use. Do not mix with other chemicals.

Do not freeze. Do not store in unmarked containers. Rinse thoroughly with water before recycling container.

TOTAL SOLUTIONS™

SPECIALTY PRODUCTS

SHIELD

Stone, Concrete and Wood
Surface Sealer

- WATER-BASED PENETRANT AND SEALER
- MAINTAINS SURFACES' NATURAL LOOK
- PROTECTS AGAINST WATER, OIL, DIRT AND GREASE
- PROTECTS AGAINST STAINS AND OTHER DAMAGE
- FOR USE INDOORS AND OUTDOORS

KEEP OUT OF REACH OF CHILDREN CAUTION

May cause eye irritation. See side panel for further precautions and first aid instructions.

NET CONTENTS:

□ 5 □ 6 □ 20 □ 30 □ 35 □ 55 Gallons

Manufactured By: Total Solutions™
PO Box 240014 • Milwaukee, WI 53224

DIRECTIONS

BEFORE APPLYING: Make sure that the surface is completely clean and dry. Test on a inconspicuous area before applying. Close off area with wet floor signs.

APPLICATION: Apply to a clean dry surface that is free of other coatings. Do not dilute product. Apply using a brush sponge, medium nap roller, or low pressure sprayer.

CURING: The polymer will be cured as soon as the surface is dry. Check to determine that curing is complete by placing a small droplet of water on the surface. If the water beads up, the sealer has satisfactorily cured.

COVERAGE: 250-500 square feet per gallon depending on the porosity of the surface. Two coats are recommended.

OPTIMUM APPLICATION TEMPERATURE: 50-90°F. The durability of the protection can be increased by heating the area after applying.

This Product Contains/CAS Number: Water/7732-18-5; Fluoropolymer Blend/Proprietary; Magnesium nitrate/10377-60-3.

NFPA® RATINGS FLAMMABILITY

HEALTH  REACTIVITY

0123•092010