

# QUICK DRY SOLVENT CLEANER

## DESCRIPTION:

This product was developed to safely remove grease, oil and tar from a variety of surfaces. It works quickly on metal parts without causing corrosive under normal conditions. Although this product is safe on most plastics and painted surfaces, be sure to test before using.

## DIRECTIONS:

**DIP TANK CLEANING:** Dip parts to be cleaned into solvent. Allow to soak until grease and grime are loosened. Remove and allow to dry.

**SPRAY CLEANING:** Spray solvent directly on parts using air gun or sprayer. Be certain to cover entire surface to be cleaned. Parts can be wiped dry or allowed to air dry. This product is ideal for use in recirculating parts washer.

VOC COMPLIANT

COLD SOLVENT

ALTERNATIVE TO  
CHLORINATED SOLVENTS

## DANGER: FLAMMABLE

Keep away from heat, sparks or open flame. Harmful if swallowed.

See side panel for additional precautions and first aid instructions.

**KEEP OUT OF REACH OF CHILDREN**

Sold By:

## DANGER: FLAMMABLE

Keep away from heat, sparks or open flame. Keep container tightly closed. Use only in a well ventilated area. Harmful if swallowed. May irritate eyes, skin or mucous membranes.

## FIRST AID

**IF SWALLOWED:** Contact a physician or poison control center immediately. DO NOT induce vomiting.

**IF IN EYES:** Flush eyes with water for at least 15 minutes. If irritation persists, contact a physician.

**IF ON SKIN:** Wash skin with soap and water. Remove all contaminated clothing and launder separately before reuse. If irritation is persistent, contact a physician.

**IF INHALED:** Remove person to fresh air. If irritation is persistent, contact a physician.

*See M.S.D.S. for complete safety information.*

**KEEP OUT OF REACH OF CHILDREN**

**HANDLING AND STORAGE:** Keep container tightly closed when not in use. Avoid excess heat and open flame. Rinse empty container before recycling container.

THIS PRODUCT CONTAINS	CAS NUMBER
Acetone .....	.67-64-1
Heptane .....	.64742-49-0
Isopropanol .....	.67-63-0

1384\*091407

NFPA® RATINGS  
Flammability



NET CONTENTS:

1  5  6  20  30  55

GALLONS