

ASPHALT PATCH is the fast, easy and economical way to make instant, traffic-ready road repairs. It keeps roads in a safe condition all year long. ASPHALT PATCH may be used in any weather, and in temperatures as low as 15°F. No involved surface preparation or primer is necessary.

Excellent for repairing asphalt, black top and stone. ASPHALT PATCH can be stored indefinitely. It will not harden until it is tamped, even if the container is not tightly closed.

DIRECTIONS

Brush dust and dirt away and fill the crack or hole with ASPHALT PATCH and tamp down.

ASPHALT PATCH

PAVING PATCH
AND POT HOLE FILLER

CAUTION

Heated material may cause burns.
May irritate eyes and skin.

See side panel for additional precautions.

KEEP OUT OF REACH OF CHILDREN

Sold By:

CAUTION

Heated material may cause burns. May irritate eyes and skin. Use with adequate ventilation.

FIRST AID

If Swallowed: Contact a physician or poison control center immediately.

If In Eyes: Flush eyes with water for at least 15 minutes. If irritation persists, obtain medical assistance.

If On Skin: Flush with water. Do not remove congealed solid material. Contact a physician.

If Inhaled: Remove person to fresh air. If irritation persists, obtain medical attention.

See M.S.D.S. for complete safety information.


KEEP OUT OF REACH OF CHILDREN

Handling & Storage: Keep container tightly closed when not in use. Do not store in unmarked containers. Rinse empty container before disposal.

This product contains:	CAS Number
Asphalt8052-42-4
Hydrogen Sulfide7783-06-4

1801.010307

NFPA® RATINGS
Flammability



NET CONTENTS: 5 GALLONS