

DESCRIPTION

Graffiti Barrier is a clear, odorless liquid that can be applied to nearly any non-porous surface to provide a protective barrier against graffiti. After it's applied, it dries to a clear film which protects against spray paint, marker, pen, and other substances. Once defaced, the barrier is easily removed with no damage to the surface. The thickened formula adheres to vertical surfaces, and is water-resistant, allowing for outdoor applications. It will not affect signs' reflective properties, and will not yellow.

Ideal for use on enameled, powder coated, electroplated, and solid plastic surfaces, including signs, lockers, bathroom partitions, vending machines, doors, walls, windows, mirrors, and surfaces that cannot be repainted if defaced.

CAUTION

May cause eye irritation. Avoid contact with eyes. Wash thoroughly after handling.

FIRST AID:

IF IN EYES: Flush eyes with water for at least 15 minutes. If irritation is persistent, contact a physician.

IF ON SKIN: Not expected to cause irritation. Wash skin with soap and water.

IF SWALLOWED: DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Contact a physician or poison control center immediately.

IF INHALED: Move person to fresh air. If irritation is persistent, contact a physician.

See *M.S.D.S.* for complete safety information.

KEEP OUT OF REACH OF CHILDREN

HANDLING AND STORAGE: Keep container tightly closed when not in use. Do not mix with other chemicals. Do not store in unmarked containers. Rinse thoroughly with water before recycling container.

TOTAL SOLUTIONS™

SPECIALTY PRODUCTS

GRAFFITI BARRIER

Sacrificial Graffiti-Protection Barrier

- CREATES A CRYSTAL-CLEAR BARRIER TO PROTECT SURFACES FROM GRAFFITI
- PAINTABLE LIQUID FORMULA CAN BE APPLIED TO MOST ANY NON-POROUS SURFACE
- IDEAL FOR SIGNS, PARTITIONS, WALLS, AND SURFACES THAT CANNOT BE REPAINTED
- WATER-RESISTANT FORMULA
- PEELABLE AND RINSABLE FOR EASY REMOVAL

KEEP OUT OF REACH OF CHILDREN

CAUTION

May cause eye irritation.

See side panel for additional precautions.

NET CONTENTS:

□ 5 □ 6 □ 20 □ 30 □ 35 □ 55 Gallons

Manufactured By: Total Solutions™
PO Box 240014 • Milwaukee, WI 53224

DIRECTIONS

Mix well before using. Using a roller or paint brush, apply a layer onto a clean, non-porous surface and allow to dry to a clear film "barrier". On vertical surfaces, rolling may be preferred over brushing in order to prevent the product from running. Start at the bottom and work up.

Allow up to 1 hour dry time. If the barrier becomes defaced, simply remove the film by peeling or with a water rinse and agitation. Reapply a new barrier once the surface has dried.

Not for use on wood, painted, and other porous surfaces. Intended for use on enameled, powder coated, electroplated, and solid plastic surfaces. In exterior applications, the barrier may wash away under extended or heavy rain.

Always test in an inconspicuous area first.

This Product Contains/CAS Number:

Water/7732-18-5; Vinyl alcohol polymers and copolymers/Mixture; Polyglycol ester/Proprietary; Hydrous silica salt/53320-86-8; Triethanolamine/102-71-6.

NFPA® RATINGS FLAMMABILITY

HEALTH  REACTIVITY