

DESCRIPTION

This sprayable rust converter instantly bonds with rust, stops its growth, transforms it into a non-rusting, paintable surface, and prevents future rust formation. It is completely safe and easy to apply.

Ideal for use on machinery, equipment, structures, vehicles, railings, marine applications and more. Non-flammable, water-based, low VOC, non-toxic, and emits no harmful fumes.

CAUTION

May be harmful if swallowed. May cause eye and skin irritation. Do not take internally. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

FIRST AID:

IF SWALLOWED: Contact physician or poison center immediately. Do not induce vomiting unless directed by medical personal. Never give anything by mouth to an unconscious person.

IF IN EYES: Flush eyes with water for at least 15 minutes. If irritation is persistent, contact a physician.

IF ON SKIN: Wash skin with soap and water. Remove all contaminated clothing and launder separately before reuse. If irritation is persistent, contact a physician.

IF INHALED: Move person to fresh air.

See M.S.D.S. for complete safety information.

KEEP OUT OF REACH OF CHILDREN

HANDLING AND STORAGE: Keep container tightly closed when not in use. Store in a cool, dry place, protected from freezing or temperatures above 100°F. For best results use product within 9 months of purchase.

IMPORTANT: DO NOT RETURN UNUSED MATERIAL TO ORIGINAL CONTAINERS

TOTAL SOLUTIONS™

SPECIALTY PRODUCTS

CONVERT

Sprayable Rust Converter

- STOPS THE SPREAD OF RUST
- CONVERTS RUST TO A PAINTABLE SURFACE
- PROTECTS AGAINST FUTURE CORROSION
- SPRAYABLE FOR EASY APPLICATION
- NON-FLAMMABLE, NON-FUMING

KEEP OUT OF REACH OF CHILDREN CAUTION

May be harmful if swallowed. May cause eye and skin irritation.
See back panel for further precautions and first aid instructions.

NET CONTENTS: One Gallon (128 fl. oz.)

Manufactured By: Total Solutions™
PO Box 240014 • Milwaukee, WI 53224

DIRECTIONS

SURFACE PREPARATION: Remove large rust and scale particles with a wire brush or sandpaper. Clean the surface thoroughly to remove dirt, dust and grease.

APPLICATION:

SHAKE OR STIR WELL BEFORE USING!

This product is ready-to-use. Do not dilute. Do not apply this product if the surface temperatures are below 50°F. Spray with an airless sprayer with 0.11-0.13 tip at 800-1200 psi. Adjust pressure as needed. One gallon will cover 200-300 square feet on a smooth, non-porous surface. Irregular, porous or textured surfaces may require more product.

DRYING TIME: The resulting coat will dry to a smooth, dark finish in 20 minutes. **Apply a second coat to ensure complete transformation of rusty surfaces.** Allow 48 hours of cure time before the application of the finished paint coat.

For long-lasting protection of iron surfaces, the cured rust converter coating should be sealed with two coats of a high quality oil-based paint. No other primer is required.

CLEAN-UP: Application equipment should be cleaned immediately with soap and water.

This Product Contains/CAS Number: Water/7732-18-5; Acrylic Latex Copolymer/Proprietary; 2-Butoxyethanol/111-76-2; Tannic Acid/1401-55-4; Ethylene Glycol/107-21-1.

NFPA® RATINGS
FLAMMABILITY

HEALTH  REACTIVITY

0347•092010