

## DESCRIPTION

This thick-bodied formula contains all natural d-Limonene for the most powerful action available. It is designed to cling to vertical surfaces for maximum performance with no waste from run-off. Contains special emulsifiers so that loosened deposits are easily flushed off with water, leaving surfaces sparkling clean and free of residue. Widely used by the roofing and asphalt (road) industries.

This heavy duty gel removes tar, pitch, asphalt, roofing compounds from tools, forms and brick, stone and masonry surfaces. It quickly strips thick and stubborn deposits from asphalt spreaders, rollers and also heating pots, paddles, buckets, brooms, shovels and other tools.

## CAUTION – COMBUSTIBLE

May be harmful if swallowed. Contains petroleum distillates. Keep away from heat or open flame. Avoid breathing vapors. Use with adequate ventilation. Avoid contact with eyes and mucous membranes. Avoid prolonged or repeated contact with skin.

### FIRST AID:

**IF IN EYES:** Flush with water for at least 15 minutes. If discomfort persists see a physician.

**IF ON SKIN:** Wash with soap and water. Remove contaminated clothing, and launder before reuse. If irritation is persistent, contact a physician.

**IF SWALLOWED:** Call a physician or poison control center immediately. Do not induce vomiting. Rinse mouth with water, then drink 1 glass of water. Never give anything by mouth to an unconscious person.

**IF INHALED:** Remove person to fresh air. Consult a physician if irritation persists.

See MSDS for complete safety information.

### KEEP OUT OF REACH OF CHILDREN

**HANDLING & STORAGE:** Keep container tightly closed when not in use. Avoid strong oxidizers, excess heat and open flame. Do not store in unmarked containers. Rinse empty container before recycling container.

# TOTAL SOLUTIONS®

INDUSTRIAL CLEANERS

## ORANGE AWAY GEL

With the Power of All Natural d-Limonene

- THICK CLINGING
- EMULSIFIABLE TAR & ASPHALT REMOVER

KEEP OUT OF REACH OF CHILDREN

## CAUTION-COMBUSTIBLE

Harmful if swallowed. Keep away from heat or open flame. See side panel for additional precautions.

### NET CONTENTS:

☐ 5 ☐ 6 ☐ 20 ☐ 30 ☐ 55 Gallons

Manufactured By: Total Solutions®  
PO Box 240014 • Milwaukee, WI 53224

## DIRECTIONS

Spray, mop or brush this product onto the area or part to be cleaned. Allow to penetrate for 10 to 15 minutes then flush away the loosened deposits with a pressure spray of water. Scrubbing with a stiff brush will speed removal of heavy accumulations. Rinse sprayers or other application equipment immediately after use.

On plastics, test this product in an inconspicuous area before use.

### This Product Contains/CAS Number:

d-Limonene/5989-27-5;  
Mineral Spirits/64742-88-7;  
Colloidal Silica/112945-52-5;  
Methyloxirane polymer w/oxirane/9003-11-6;  
Ethylene glycol/ 107-21-1.

NFPA® RATINGS  
FLAMMABILITY

HEALTH  REACTIVITY

0388•091310