

DESCRIPTION

This multi-purpose cleaner and degreaser contains 15% butyl along with special detergents and builders for superior performance in hot or cold water. It instantly dissolves the heaviest dirt, grime, oil, and grease deposits.

CAUTION

Maybe harmful if swallowed. May cause eye and skin irritation. Do not take internally. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

FIRST AID:

IF SWALLOWED: Contact a physician or poison control center immediately. DO NOT induce vomiting.

IF IN EYES: Flush eyes with water for at least 15 minutes. If irritation is persistent, contact a physician.

IF ON SKIN: Wash skin with soap and water. Remove all contaminated clothing and launder separately before reuse. If irritation is persistent, contact a physician.

IF INHALED: Move person to fresh air. If irritation is persistent, contact a physician.

See M.S.D.S. for complete safety information.

KEEP OUT OF REACH OF CHILDREN

HANDLING AND STORAGE: Keep container tightly closed when not in use. Do not mix with other chemicals. Do not store in unmarked containers. Rinse thoroughly with water before recycling container.

NFPA® RATINGS
FLAMMABILITY



TOTAL SOLUTIONS™

INDUSTRIAL CLEANERS
and DEGREASERS

SUPER SOLV #2

Concentrate Cleaner
with 15% Butyl

- REMOVES THE HEAVIEST DIRT AND GREASE BUILD-UPS

KEEP OUT OF REACH OF CHILDREN

CAUTION

May be harmful if swallowed.
May cause eye and skin irritation. See side panel for additional precautions and first aid instructions.

NET CONTENTS:

□ 5 □ 6 □ 20 □ 30 □ 55 Gallons

Manufactured By: Total Solutions™
PO Box 240014 • Milwaukee, WI 53224

DIRECTIONS

Dilute in warm or hot water for best performance. Spray, brush or mop on and allow the cleaner to penetrate and loosen deposits. Rinse with clean water.

To remove difficult or hard deposits, allow the solution to saturate the surface for approximately 5 minutes, then rub gently with steel wool and rinse.

USE DILUTION A FOR: Wax on asphalt tile, vinyl floors, terazzo, concrete, and all other hard and resilient floors.

USE DILUTION B FOR: Auto, bus, truck and equipment parts, engines, transmissions and chassis, ovens, fryers and grills, kitchen hoods, and air filters.

USE DILUTION C FOR: Fans and ducts, counter and hoods, motor shells, greasy parts, brick walls, skylights, and refrigerator and air conditioner coils.

USE DILUTION D FOR: Walls, greasy floors, gymnasiums, whitewall tires, rubber and wooden mats, floor machine pads and brushes, swimming pools, spas, and shower rooms.

USE DILUTION E FOR: Vinyl, rubber, linoleum tile, ceramic, and terazzo and concrete floors.

USE DILUTION F FOR: Lockers, files, cabinets, painted surfaces, and light cleaning on decorative surfaces.

DILUTIONS		
APPLICATION	PARTS OF CONCENTRATE	PARTS OF WATER
A	1	up to 12
B	1	up to 15
C	1	up to 24
D	1	up to 64
E	1	up to 100
F	1	up to 128

This Product Contains/CAS Number:
Water/7732-18-5; 2-Butoxyethanol/111-76-2; Coco Diethanolamide/67785-13-1; Tetrapotassium Pyrophosphate/7320-34-5; Sodium Xylenesulfonate/1300-72-7.

0418.011011