

DESCRIPTION

This concentrated alkaline cleaner rapidly penetrates, loosens, and removes soil deposits, grease and oils, dissolves quickly and rinses freely. It is ideal for use on ferrous and most non-ferrous metals found in auto service shops on engine blocks and radiators, in boilers and heat exchangers, in food processing establishments, machine shops and industrial use.

DANGER POISON

May be fatal if swallowed. Causes eye and skin burns. Respiratory tract irritation. Do not take internally. Do not get in eyes or skin. Avoid breathing dust. Keep container tightly closed. Use only with adequate ventilation. Wash thoroughly after handling.

FIRST AID:

IF SWALLOWED: Contact a physician immediately. Do not induce vomiting. Never give anything to an unconscious person.

IF IN EYES: Flush eyes and under eyelids with cool water for at least 15 minutes and obtain medical attention.

IF ON SKIN: Wash with soap and water. Remove contaminated clothing and launder before reuse. If irritation is persistent, contact a physician.

IF INHALED: Move person to fresh air. Call a physician immediately.

See M.S.D.S. for complete safety information.

KEEP OUT OF REACH OF CHILDREN

HANDLING AND STORAGE: Keep container tightly closed when not in use. Do not mix with other chemicals. Do not store in unmarked containers. Rinse thoroughly with water before recycling container.

TOTAL SOLUTIONS™

INDUSTRIAL CLEANERS
and DEGREASERS

STEAM & HOT TANK CLEANER

Removes Soils, Greases
and Oils

- PENETRATES THE HEAVIEST SOILS
- DISSOLVES QUICKLY
- RINSES FREELY

DANGER POISON

May be fatal if swallowed.
Causes eye and skin burns. Respiratory tract irritation.

See side panel for additional precautions.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: □ 25 □ 50 □ 100 LBS.

Manufactured By: Total Solutions™
PO Box 240014 • Milwaukee, WI 53224

DIRECTIONS

For normal cleaning, dissolve 16 ounces in 3 gallons of water. For extremely soiled surfaces, or heavy deposits, a stronger solution may be required. For best results, the temperature of the hot tank should be maintained between 180°F and 190°F.

This Product Contains/CAS Number: Sodium Carbonate/497-19-8; Sodium Metasilicate/6834-92-0; Sodium Tripolyphosphate/7758-29-4; Sodium Hydroxide/1310-73-2; Poly (Oxyethylene) Nonylphenol/9016-45-9.

NFPA® RATINGS
FLAMMABILITY

HEALTH  REACTIVITY
SPECIAL