# **Aluminum Transmission & Engine Cleaner**

Product # 663

# Concentrated and Soluble Powder

Designed to function most efficiently at elevated temperatures. Cleans and strips away oil, grease and other deposits from transmissions, radiators, and other metal parts without foaming problems. It will not leave a film or residue on parts and it will not plug up spray cabinets' jets, or build-up inside the spray cabinet

# Cleans:

- Transmission
- Engines

Radiators

Metal Parts

# **Effective Against:**

- Grease
- Oils

Deposits

# Features and Benefits

- Generates less waste than solvent cleaning
- · Contains rust inhibitors to prevent flash rusting
- Effectively inhibits the growth of mold and mildew and the odors caused by them.

**Properties** 

Application...... Spay Cabinets and Dip Tanks

**Directions** Complete directions on product label

For Spray Cabinets: Dilute 1-2 ounces per gallon of water.

Maintain temperature at 190°F for best results.

For Dip Tanks: Dilute 1 ounce per gallon of water. Let

parts soak for 15-20 minutes and then rinse.

### 

Socialii Triporypriospriate	1130-29-4
Sodium Metasilicate	6834-92-0
Sodium Sulfate	7757-82-6
Sodium Carbonate	497-19-8
Sodium Dichloroisocyanurate.	51580-86-0

# Safety

Warning. Harmful if swallowed. Eye and skin irritant. Keep out of the reach of children

# **DOT Shipping (ground transportation)**

Proper Shipping Name: Corrosive solid, basic, inorganic, n.o.s.

(sodium metasilicate, anhydrous)

Class: 8

ID Number: UN 3262

Package Group: III

# NFPA RATINGS Flammability Health Reactivity

## Quantities

100 pounds

50 pounds

25 pounds

