

DESCRIPTION

Freezing agents combined to give fast, easy removal of gum and wax deposits from carpet, upholstery, floors, furniture, walls, staircases and chairs. Leaves no residue.

CAUTIONS: Prolonged or repeated contact can result in defatting and drying of the skin. Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful. Do not get this material in contact with eyes or skin. Keep away from heat, sparks and flames. Do not puncture or incinerate container. Do not expose to heat or store above 120°F (49°C) as container may burst. Avoid prolonged exposure to sunlight. Use with adequate ventilation.

FIRST AID:

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

SKIN: Wash off with warm water and soap. Get medical attention if irritation develops or persists.

INHALATION: Move to fresh air. Call a physician if symptoms develop or persist.

INGESTION: If material is ingested, immediately contact a poison control center. Rinse mouth. Do not induce vomiting with advice from poison control center. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.

KEEP OUT OF REACH OF CHILDREN

See Material Safety Data Sheet for complete safety information.

TOTAL SOLUTIONS™

RESILIENT FLOOR CARE

CHEWING GUM REMOVER

Freeze Action

- CAN ALSO BE USED EFFECTIVELY FOR REMOVING CANDLE WAX, PUTTY AND OTHER GUMMY SUBSTANCES
- LEAVES NO RESIDUE

WARNING:
FLAMMABLE. EYE IRRITANT.
CONTENTS UNDER PRESSURE.

See side panel for further precautions and first aid instructions.

NET WT. 6.5 OZ. (184 g)

Distributed By: Total Solutions™
PO Box 240014 • Milwaukee, WI 53224

DIRECTIONS

First remove all material possible with a scraper or dull knife. Hold snorkel tube about 2 inches from substance and spray with a 5-10 second blast. While material is hard and brittle, scrape rapidly with a dull knife or scraper. Repeat as necessary.

This Product Contains/CAS Number:

Ethyl Alcohol/64- 17-5; Liquefied Petroleum Gas/68476-86-8.

HMIS® RATINGS: HEALTH - 1, FLAMMABILITY - 4, PHYSICAL HAZARD - 0, PERSONAL PROTECTION - X.

CONTAINS NO OZONE DEPLETING CHEMICALS!
CONTAINS NO CFC'S OR HCFC'S!

8104.010412

