

## DESCRIPTION

Use to remove wax build-up from baseboards, floors and ceramic wall tiles.

## CAUTIONS:

Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful. Do not get this material in contact with eyes or skin. Keep away from heat, sparks and flames. Do not puncture, incinerate or crush. Do not expose to heat or store at temperatures above 120°F (49°C) as container may burst. Avoid prolonged exposure to sunlight. Use with adequate ventilation.

### FIRST AID:

**EYES:** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

**SKIN:** Immediately flush skin with plenty of water. Get medical attention immediately.

**INHALATION:** Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Get medical attention immediately.

**INGESTION:** Immediately contact a poison control center. Have victim rinse mouth thoroughly with water. Do not induce vomiting without advice from poison control center. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.

See M.S.D.S. for complete safety information.

**KEEP OUT OF REACH OF CHILDREN**  
CONTAINS NO OZONE DEPLETING  
CHEMICALS!

# TOTAL SOLUTIONS™

RESILIENT FLOOR CARE

## BASEBOARD STRIPPER

Removes Heavy  
Wax Build-Up In  
Hard To Reach Areas

- FLOORS, BASEBOARDS,  
CERAMIC WALL TILE
- CLINGING FOAM ADHERES  
TO SURFACES
- EASY RINSING
- USE IN UPSIDE DOWN POSITION

## CAUTION

MAY CAUSE EYE IRRITATION.  
CONTENTS UNDER PRESSURE.  
Read carefully other cautions on back panel.  
**KEEP OUT OF REACH OF CHILDREN**

NET WT. 19 oz. (1 lb. 3 oz.) 539 g

Distributed By: Total Solutions™  
PO Box 240014 • Milwaukee, WI 53224

## DIRECTIONS

SHAKE WELL BEFORE USING.

Check the product on a small inconspicuous area of the surface to be sprayed to make sure there is no attack. Do not spray on painted or varnished surfaces. Wipe off any overspray immediately.

Turn can UPSIDE DOWN and hold 6-10 inches from baseboard or surface to be sprayed. A thin even coating should cover the wax.

Wait 3 to 5 minutes, longer in case of substantial build-up. Wet scrub the surface with an abrasive pad or scrub brush. Repeat until all wax is removed.

Rinse surface with clean water and allow area to dry thoroughly before re-polishing.

### This Product Contains/CAS

**Number:** Water/7732-18-5;  
2-Butoxyethanol/111-76-2; Alkyl  
Phenol Ethoxylate Phosphate  
Ester/68412-53-3; Liquefied  
Petroleum Gas/68476-86-8.

**HMIS® RATINGS:** HEALTH - 1,  
FLAMMABILITY - 2, PHYSICAL  
HAZARD - 0, PERSONAL  
PROTECTION - X.

8177.011012