

## DESCRIPTION

When applied to any rusty surface, it will convert the residual rust to a black protective polymeric coating. This inert protective coating prevents further rusting and corrosion.

### **DANGER: EXTREMELY FLAMMABLE**

May cause burns and/or severe irritation to the eyes, skin, stomach and respiratory tract. Prolonged or repeated contact may dry or defat the skin and lead to inflammation (i.e. dermatitis). Possible aspiration hazard - may cause inflammation of the lungs. May cause nausea, vomiting, pain, and stomach upset (e.g., diarrhea). May affect the following organs upon prolonged or repeated overexposure: Liver. Kidneys. Nervous system. Heart and/or circulatory system. Keep away from heat, sparks, and flames. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F (49°C) as container may burst. Avoid prolonged exposure to sunlight. Use with adequate ventilation.

#### **FIRST AID:**

**IF IN EYES:** Flush eyes and under eyelids with water for at least 15 minutes. Obtain medical attention.

**IF ON SKIN:** Flush skin with plenty of water for 15 minutes. Remove contaminated clothing, and launder before reuse. If irritation is persistent, contact a physician.

**IF SWALLOWED:** Contact physician or poison control center immediately. Rinse mouth with water and give affected person 1-2 glasses of water to dilute. Do not induce vomiting unless instructed by a physician or poison control center. Never give anything by mouth to an unconscious person.

**IF INHALED:** Remove person to fresh air. If symptoms develop, seek medical attention. If not breathing, give artificial respiration.

#### **KEEP OUT OF REACH OF CHILDREN**

See Material Safety Data Sheet for complete safety information.

CONTAINS NO OZONE  
DEPLETING CHEMICALS!

# TOTAL SOLUTIONS™

SPECIALTY PRODUCTS

## RUST CONVERTER

Converts Rust To Form A Stable Paintable Surface

- ELIMINATES THE NEED FOR SCRAPING, SANDBLASTING OR PRIMING RUSTY SURFACES

- PROTECTS FURTHER RUSTING ON SURFACES EXPOSED TO RAIN, SUN AND SALT SPRAY

**KEEP OUT OF REACH OF CHILDREN**

### **DANGER:**

**EXTREMELY FLAMMABLE.  
MAY CAUSE BURNS TO EYES,  
SKIN AND RESPIRATORY TRACT.  
CONTENTS UNDER PRESSURE.**

Read side panel for additional precautions.

NET WEIGHT: 13 oz. (369 g)

Distributed By: Total Solutions™  
PO Box 240014 • Milwaukee, WI 53224

## DIRECTIONS

For best results prepare surface by brushing the loose rust from the surface using a wire brush or sand paper. Clean the surface to remove grease and grime. Shake well before use.

Hold can 8-12 inches from surface and spray a thin coat onto the surface. After the surface has dried, it will turn black. Then apply a second thin coat. Allow 48 hours to completely cure before painting while protecting it from rain or dew.

For long lasting protection, seal with two coats of a high quality oilbased paint.

Do not apply if the surface temperature is below 50°F or above 90°F. Store in a cool dry place, protected from freezing or temperatures above 100°F.

#### **This Product Contains/CAS Number:**

Acetone/67-64-1; Isopropanol/67-63-0; Ethylene Glycol/107-21-1; Tannic Acid/1401-55-4; Oxalic acid/144-62-7; Dimethyl Ether/115-10-6; Liquefied Petroleum Gas/68476-86-8.

**HMS RATINGS:** Health - 2;  
Flammability - 4; Physical Hazard - 0.

8346•010512