

DESCRIPTION

Improves nighttime safety and awareness by creating a bright, reflective coating on most any surface. Applies semi-transparent. Under direct light, thousands of tiny reflective glass beads create powerful brightness.

Provides greater visibility to objects including mailboxes, bicycles, house numbers, water valves, rocks, steps, fences, curbs, railings, trailers, autos, RVs, snowmobiles, motorcycles, boats, running shoes and clothes, pet collars, safety vests, clothing, helmets, signs, buoys, and many others. Works on fabric, asphalt, concrete, masonry, rubber, plastic, stucco, and wood.

Warning: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

DANGER

EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. Harmful if swallowed. May cause eye and skin irritation. Do not take internally. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep away from heat, sparks and flame. Use only with adequate ventilation. Store in a cool dry place away from heat.

FIRST AID:

IF SWALLOWED: Call a poison control center or doctor immediately. Do not induce vomiting.

IF IN EYES: Flush eyes with water for at least 15 minutes.

IF ON SKIN: Wash skin with soap and water. Remove all contaminated clothing and launder separately before reuse. If irritation is persistent, contact a physician.

IF INHALED: Move person to fresh air. If irritation is persistent, contact a physician.

See M.S.D.S. for complete safety information.

KEEP OUT OF REACH OF CHILDREN

TOTAL SOLUTIONS™

SPECIALTY PRODUCTS

REFLECTBACK

Creates a Bright Reflective Coating

- GREATLY IMPROVES NIGHTTIME SAFETY AND AWARENESS
- CREATES A BRIGHT REFLECTION UNDER DIRECT LIGHT SOURCES
- APPLIES SEMI-TRANSPARENT TO MOST ALL SURFACES
- IMBEDDED GLASS BEADS PROVIDE A REFLECTION UNMATCHED BY OTHER PRODUCTS

KEEP OUT OF REACH OF CHILDREN

DANGER

EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. Harmful if swallowed. May cause eye and skin irritation. CONTENTS UNDER PRESSURE. See other cautions on back panel.

NET WT.: 12 oz.

Manufactured By: Total Solutions™
PO Box 240014 • Milwaukee, WI 53224

DIRECTIONS

Test in an inconspicuous area first. Apply to a clean, dry surface. Remove any dirt, rust, wax, grease, and other debris. Protect surrounding area from overspray. Shake can before use. Hold can at least 12" from surface to be coated. Spray in short, overlapping strokes. A mist spray will provide superior results compared to a heavy spray. For larger areas, apply several thin coats. **DO NOT OVER APPLY!** Apply in temperatures between 40° (F) and 90° (F). One can covers approximately 15 sq. ft. Surface dries in 10 minutes. To clean nozzle after use, turn can upside down and spray until valve clears.

This Product Contains/CAS Number:

Glass Beads/65997-17-3; Toluene/108-88-3; Methyl Acetate/79-20-9; Dimethyl Ether/115-10-6; Propane/74-98-6.

NFPA® RATINGS
FLAMMABILITY

HEALTH 2 4 0 REACTIVITY

8389.020911