Safety Data Sheet



SECTION 1: Product and company identification

Product name : Carpet/Upholstery Spot Remover

Use of the substance/mixture : Cleaner Product code : 8410

Company : Total Solutions P.O. Box 240014

Milwaukee, WI 53224 - USA

T (414) 354-6417

Emergency number : Chemtec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Aerosol 1 H222 Skin Irrit. 2 H315 Eye Irrit. 2A H319

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)





GHS02

GHS07

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Extremely flammable aerosol

Causes skin irritation
Causes serious eye irritation

Precautionary statements (GHS-US) : Keep away from heat, Do not smoke, open flames, sparks. - No smoking

Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use

Wash thoroughly after handling

Wear eye protection, face protection, protective gloves

If on skin: Wash with plenty of water

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing

Specific treatment (see first aid on this label)
If skin irritation occurs: Get medical advice/attention
If eye irritation persists: Get medical advice/attention
Take off contaminated clothing and wash it before reuse

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
2-butoxyethanol, ethylene glycol monobutyl ether, butyl cellosolve	(CAS No) 111-76-2	2.5 - 10	Not classified
butane	(CAS No) 106-97-8	2.5 - 10	Flam. Gas 1, H220 Compressed gas, H280
2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	(CAS No) 112-34-5	2.5 - 10	Eye Irrit. 2A, H319

Date of issue: 10/27/2015 Revision date: 06/01/2015 Version: 1.0 P GHS SDS Page 1 of 6

Safety Data Sheet



Name	Product identifier	%	Classification (GHS-US)
propane	(CAS No) 74-98-6	1 - 2.5	Flam. Gas 1, H220
			Compressed gas, H280

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect

themselves

Remove the victim into fresh air. Call a POISON CENTER or doctor/physician if you feel unwell. First-aid measures after inhalation

First-aid measures after skin contact Take off immediately all contaminated clothing and wash it before reuse. Wash with water and soap.

If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion Rinse mouth. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after skin contact : Causes skin irritation. Symptoms/injuries after eye contact : Causes serious eve irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water fog. Dry chemical powder. Carbon dioxide.

Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

5.2. Special hazards arising from the substance or mixture

Fire hazard : May liberate toxic gases. Extremely flammable aerosol.

Explosion hazard : Contents under pressure. Contains gas under pressure; may explode if heated. Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

5.3. Advice for firefighters

: Move containers away from the fire area if this can be done without risk. Cool tanks/drums with Firefighting instructions

water spray/remove them into safety.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures Evacuate unnecessary personnel. Stay upwind/keep distance from source. No flames, No sparks.

Eliminate all sources of ignition.

6.1.1. For non-emergency personnel

Protective equipment : Do not enter without an appropriate protective equipment.

DO NOT touch spilled material. Ventilate spillage area. Advice local authorities if considered **Emergency procedures**

necessary

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid discharge to the environment. Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

: Eliminate every possible source of ignition. Stop leak if safe to do so. Move the cylinder to a safe and For containment

open area if the leak is irreparable. Clean up any spills as soon as possible, using an absorbent

material to collect it.

: Clean thoroughly. Methods for cleaning up

Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed Keep away from heat, sparks and flame. Pressurized container: Do not pierce or burn, even after

use. Do not use if spray button is missing or defective.

Date of issue: 10/27/2015 Revision date: 06/01/2015 Version: 1.0 P GHS SDS Page 2 of 6

Safety Data Sheet

TOTAL SOLUTIONS

Precautions for safe handling : Ground/bond container and receiving equipment. Use only non-sparking tools. Use explosion-proof

equipment. Do not spray on a naked flame or any incandescent material. Use only outdoors or in a well-ventilated area. Ensure good ventilation of the work station. Avoid breathing dust, fume, gas, mist, spray, vapors. Avoid contact with skin, eyes and clothing. Do not re-use empty containers. Use

personal protective equipment as required.

Hygiene measures : Use good personal hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Pressurized container. Do not puncture, incinerate or crush.

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from

heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store in a well-

ventilated place.

Storage area : Aerosol 1.

Special rules on packaging : meet the legal requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-butoxyethanol, ethylene glycol monobutyl ether, butyl cellosolve (111-76-2)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr
butane (106-97-8)		
ACGIH	ACGIH TWA (ppm)	1000 ppm
ACGIH	ACGIH STEL (ppm)	1000 ppm
2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether (112-34-5)		
ACGIH	ACGIH TWA (ppm)	10 ppm
propane (74-98-6)		
ACGIH	ACGIH TWA (ppm)	1000 ppm
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

8.2. Exposure controls

Appropriate engineering controls : Provide sufficient air exchange and/or exhaust. Emergency eye wash fountains and safety showers

should be available in the immediate vicinity of any potential exposure.

Hand protection : Gloves

Eye protection : Chemical goggles or safety glasses. Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Thermal hazard protection : Use appropriate personal protective equipment when risk assessment indicates this is necessary.

Consumer exposure controls : When using do not smoke. Use good personal hygiene practices. Wash hands and other exposed

areas with mild soap and water before eat, drink or smoke and when leaving work. Take off

contaminated clothing and wash before reuse.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Clear, colorless liquid. Aerosol.

Odor : Butyl

Odor threshold : No data available
pH : 11 - 12.5 Estimated
Melting point : No data available
Freezing point : No data available
Boiling point : 222.87 °F Estimated

Flash point : -156 °F Propellant estimated

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available Explosion limits : No data available Explosive properties : No data available

Date of issue: 10/27/2015 Revision date: 06/01/2015 Version: 1.0 P GHS SDS Page 3 of 6

Safety Data Sheet



Oxidizing properties No data available Vapor pressure : No data available Relative density No data available Relative vapor density at 20 °C : No data available Specific gravity / density 0.99 - 1 g/ml Estimated Solubility No data available Log Pow No data available Log Kow No data available Auto-ignition temperature : 230 °C Estimated Decomposition temperature : No data available No data available Viscosity Viscosity, kinematic No data available Viscosity, dynamic : No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Hazardous polymerization does not occur.

10.4. Conditions to avoid

Heat. Sparks. Open flame.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

2-butoxyethanol, ethylene glycol monobutyl ether, butyl cellosolve (111-76-2)	
ATE CLP (oral)	500.000 mg/kg body weight
ATE CLP (dermal)	1100.000 mg/kg body weight
ATE CLP (dust, mist)	1.500 mg/l/4h

Skin corrosion/irritation Causes skin irritation.

pH: 11 - 12.5 Estimated

Serious eye damage/irritation Causes serious eye irritation.

pH: 11 - 12.5 Estimated

Respiratory or skin sensitization Not classified Not classified Germ cell mutagenicity Carcinogenicity Not classified Reproductive toxicity Not classified Specific target organ toxicity (single exposure) Not classified Specific target organ toxicity (repeated

exposure)

Not classified

Aspiration hazard : Not classified Symptoms/injuries after skin contact Causes skin irritation. Symptoms/injuries after eye contact : Causes serious eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

Date of issue: 10/27/2015 Page 4 of 6 Revision date: 06/01/2015 Version: 1.0 P GHS SDS

Safety Data Sheet



12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

: Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

This material and its container must be disposed of in a safe manner. Handle unclean empty Additional information

containers as full ones.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950 Proper Shipping Name (DOT) : Aerosols

> flammable, (each not exceeding 1 L capacity) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Transport hazard class(es) (DOT) Hazard labels (DOT) : 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None DOT Special Provisions (49 CFR 172.102) : N82 DOT Packaging Exceptions (49 CFR : 306

173.xxx)

DOT Quantity Limitations Passenger

aircraft/rail (49 CFR 173.27)

: 75 kg

DOT Quantity Limitations Cargo aircraft : 150 kg only (49 CFR 175.75)

DOT Vessel Stowage Location

: A

DOT Vessel Stowage Other

: 25 - Shade from radiant heat,87 - Stow "separated from" Class 1 (explosives) except Division

14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Additional information

: This product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D Other information

utilizing the exception found at 49 CFR 173.306.

ADR

No additional information available

Transport by sea

UN-No. (IMDG) : UN1950 Proper Shipping Name (IMDG) : Aerosols

Class (IMDG) : 2.1 - Flammable gases

Air transport

: UN1950 UN-No.(IATA)

Proper Shipping Name (IATA) : Aerosols, Flammable Class (IATA) : 2.1 - Gases : Flammable

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Date of issue: 10/27/2015 Revision date: 06/01/2015 Version: 1.0 P GHS SDS Page 5 of 6

Safety Data Sheet



butane (106-97-8)			
Not listed on SARA Section 313 (Specific toxic che	emical listings)		
propane (74-98-6)			
Not listed on SARA Section 313 (Specific toxic che	emical listings)		

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.


Full text of H-phrases:

At of 11 princeoo.	
Compressed gas	Gases under pressure Compressed gas
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Aerosol 1	Flammable aerosol Category 1
Flam. Gas 1	Flammable gases Category 1
Skin Irrit. 2	Skin corrosion/irritation Category 2
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H280	Contains gas under pressure; may explode if heated
H315	Causes skin irritation
H319	Causes serious eye irritation

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.

 Date of issue: 10/27/2015
 Revision date: 06/01/2015
 Version: 1.0
 P GHS SDS
 Page 6 of 6