

SECTION 1: Product and company identification

Product name : Metalworking Coolant & Lube
 Use of the substance/mixture : Lubricant
 Product code : 0303
 Company : Total Solutions
 P.O. Box 240014
 Milwaukee, WI 53224 - USA
 T (414) 354-6417
 Emergency number : Chemtrec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin Irrit. 2 H315
 Eye Irrit. 2 H319

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS07

Signal word (GHS-US) : Warning
 Hazard statements (GHS-US) : Causes skin irritation
 Causes serious eye irritation
 Precautionary statements (GHS-US) : Wash thoroughly after handling
 Wear eye protection, protective clothing, protective gloves.
 If on skin: Wash with plenty of soap and water.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Specific treatment (see First aid measures on this label)
 If skin irritation occurs: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

Full text of H-phrases: see section 16

3.2. Mixtures

| Name | Product identifier | % | GHS-US classification |
|----------------|--------------------|-----|---|
| diethanolamine | (CAS-No.) 111-42-2 | 1-5 | Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Carc. 2, H351 STOT RE 2, H373 |
| ethanolamine | (CAS-No.) 141-43-5 | 1-5 | Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 STOT SE 3, H335 |

A specific chemical identity and/or percentage of composition has been withheld as a trade secret. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).
 First-aid measures after inhalation : Remove the victim into fresh air.

Metalworking Coolant & Lube

Safety Data Sheet



- First-aid measures after skin contact : Take off contaminated clothing and wash it before reuse. Wash with water and soap. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth with water. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : None under normal use.
- Symptoms/effects after skin contact : Causes skin irritation.
- Symptoms/effects after eye contact : Causes serious eye irritation.
- Symptoms/effects after ingestion : Gastrointestinal complaints. Nausea. Vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : All extinguishing media allowed.

5.2. Special hazards arising from the substance or mixture

- Reactivity : Thermal decomposition may produce oxides of carbon and nitrogen.

5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Take account of environmentally hazardous firefighting water.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Isolate from fire, if possible, without unnecessary risk.

6.1.1. For non-emergency personnel

- Protective equipment : Protective goggles. Gloves. Protective clothing.
- Emergency procedures : Evacuate unnecessary personnel. Avoid contact with skin, eyes and clothing. Ventilate spillage area.

6.1.2. For emergency responders

- Protective equipment : Use personal protective equipment as required.
- Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Contain released product, pump into suitable containers.
- Methods for cleaning up : This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Comply with the legal requirements. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Do not get in eyes, on skin, or on clothing.
- Hygiene measures : Wash thoroughly after handling. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations.
- Storage conditions : Keep container closed when not in use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Incompatible products : Acids. Strong oxidizers.
- Information on mixed storage : KEEP SUBSTANCE AWAY FROM: (strong) acids.
- Storage area : Meet the legal requirements. Store in a cool area. Store in a dry area.

SECTION 8: Exposure controls/personal protection

Metalworking Coolant & Lube

Safety Data Sheet

8.1. Control parameters

| ethanolamine (141-43-5) | | |
|---------------------------|-------------------------------------|---------------------|
| ACGIH | ACGIH TWA (ppm) | 3 ppm |
| ACGIH | ACGIH STEL (ppm) | 6 ppm |
| ACGIH | Remark (ACGIH) | Eye & skin irr |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 6 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 3 ppm |
| diethanolamine (111-42-2) | | |
| ACGIH | ACGIH TWA (mg/m ³) | 1 mg/m ³ |
| ACGIH | Remark (ACGIH) | Liver & kidney dam |

8.2. Exposure controls

Personal protective equipment : Safety glasses. Protective clothing. Gloves. Use appropriate personal protective equipment when risk assessment indicates this is necessary.



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|-----------------------|
| Physical state | : Liquid |
| Appearance | : clear. Gold. brown. |
| Odor | : Mild odor |
| Odor threshold | : No data available |
| pH | : 9 – 11 |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : > 200 °F Closed Cup |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Flammability (solid, gas) | : No data available |
| Explosion limits | : No data available |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |
| Vapor pressure | : No data available |
| Relative density | : No data available |
| Relative vapor density at 20 °C | : No data available |
| Specific gravity / density | : 1.05 g/ml |
| Solubility | : Soluble in water |
| Log Pow | : No data available |
| Log Kow | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| VOC content | : < 6 % |

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition may produce oxides of carbon and nitrogen.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

Metalworking Coolant & Lube

Safety Data Sheet



10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Acids. Oxidizing agent.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

| ethanolamine (141-43-5) | |
|--------------------------------|------------------------|
| LD50 oral rat | 1720 mg/kg female |
| LD50 dermal rabbit | 1000 mg/kg |
| ATE CLP (oral) | 1720 mg/kg body weight |
| ATE CLP (dermal) | 1000 mg/kg body weight |
| ATE CLP (gases) | 4500 ppmV/4h |
| ATE CLP (vapors) | 11 mg/l/4h |
| ATE CLP (dust, mist) | 1.5 mg/l/4h |

| diethanolamine (111-42-2) | |
|----------------------------------|------------------------|
| LD50 dermal rabbit | 8180 mg/kg |
| ATE CLP (oral) | 500 mg/kg body weight |
| ATE CLP (dermal) | 8180 mg/kg body weight |

Skin corrosion/irritation : Causes skin irritation.
pH: 9 - 11

Serious eye damage/irritation : Causes serious eye irritation.
pH: 9 - 11

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

| diethanolamine (111-42-2) | |
|----------------------------------|--------------------------------------|
| IARC group | 2B - Possibly carcinogenic to humans |

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified

Symptoms/effects after inhalation : None under normal use.

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : Gastrointestinal complaints. Nausea. Vomiting.

Likely routes of exposure : Skin and eye contact

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT : Not regulated for transport

Metalworking Coolant & Lube

Safety Data Sheet

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

| | | |
|----------------|------------------|------|
| Diethanolamine | CAS-No. 111-42-2 | 1-5% |
|----------------|------------------|------|

| | |
|---|--------|
| diethanolamine (111-42-2) | |
| Subject to reporting requirements of United States SARA Section 313 | |
| CERCLA RQ | 100 lb |



WARNING

This product can expose you to diethanolamine, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.


Full text of H-phrases:

| | |
|------|---|
| H227 | Combustible liquid |
| H302 | Harmful if swallowed |
| H312 | Harmful in contact with skin |
| H314 | Causes severe skin burns and eye damage |
| H315 | Causes skin irritation |
| H318 | Causes serious eye damage |
| H332 | Harmful if inhaled |
| H335 | May cause respiratory irritation |
| H351 | Suspected of causing cancer |
| H373 | May cause damage to organs through prolonged or repeated exposure |

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.