DESCRIPTION

This product is a blend of volatile neutralizing amines formulated to provide corrosion protection in steam condensate systems and associated power equipment. Regular usage provides pH adjustment to untreated steam condensate, in high and low pressure systems, to prevent the formation of harmful acids. It provides excellent protection to return lines, reducing the iron and copper content of the condensate.

DIRECTIONS

Dosages of this product will vary depending upon size and usage of system, steam flow and amount of corrosive gases present or released.

In order to assure adequate protection this product should be mixed with water and fed on a continuous basis directly into the boiler or feedwater system.

May be fed in a chemical mixing tank with other water treatment chamicals like scale and corrosion inhibitors and oxygen scavengers.

Control of product should be maintained so that condensate pH is above 8.0 and iron levels are negligible.

STEAM TREAT

PROTECTS CONDENSATE LINES AGAINST ACIDIO CORROSION

PROTECTS BOTH HIGH AND LOW

CAUTION:

May be harmful if swallowed.
See back panel for further precautions and first aid instructions.

KEEP OUT OF REACH OF CHILDREN

SOLD BY:

CAUTION

May be harmful if swallowed hritant. Do not take internally. Avoid contact with skin, eyes, and mucous membranes.

,Pyrst Aud:

of water and induce vomiting. Obtain immediate medical assistance.

If In Eyes: Flush with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical assistance.

If On Skin: Wash thoroughly with soap and water.

KEEP OUT OF REACH OF CHILDREN

This Product Contains	CAS Number
Water	7732-18-5
Cyclohexylamine	
Diethylethanolamine	
Polyalkylene Glycol	9038-95-2

1928.92809

NET CONTENTS:

5 6 20 30 35 55 GALLONS