#### Oil-based coolant & lube

This ready-to-use oil is formulated with a unique blend of lubricants and additives to make it the ideal choice for machining, tapping, boring and thread cutting operations. It readily clings to the cutting bit to provide excellent residual lubrication and rapid heat removal, extending the working life of tools and equipment. It also provides for better workpiece visibility and protects against rust.

### Use for:

- Drilling,
- Milling
- **Tapping**
- High-carbon steels Not recommended for use on copper or aluminum.
- Threading
  - Stainless steel

Cutting

Boring

- Machining Tools
- Grinding
- Sawing
- Hard alloys

### Features and Benefits

- Extends tool life and improves productivity.
- Promotes residual lubrication, cleaner cuts, smoother finishes and cooler tool temperatures.
- Especially useful in all milling, boring, cutting, grinding, tapping, threading, sawing and machining operations.

### **Properties** Appearance.....

Black liquid

Sulfur

Ready-to-use..... Yes Specific gravity..... 0.90

Fragrance.....

Flash point..... 320° F

Stability..... 1 vear

Solubility..... Insoluble in water

## **Directions** Complete directions on product label

**CAS Number** 

**Proprietary** 

Proprietary **Proprietary** 

Ready to use, no dilutions recommended.

# **Active Ingredients**

Proprietary Additives .....

Chlorinated Paraffin .....

Mineral Oil .....

## Safety

Warning: Harmful or fatal if swallowed. Keep out of the reach of children.

## **DOT Shipping** (ground transportation)

Proper Shipping Name: None Class: None ID Number: None Package Group: None

## **NFPA RATINGS** Flammability Health 4 Reactivity

### Quantities

55 gallon

35, 30 & 20 gallon

5 or 6 gallon

6 X 1 gallon

4 X 1 gallon







