

# SILT & SAND REMOVER

This flushing aid is designed to break up and disperse all types of organic debris and inorganic deposits that accumulate in sewer and drain pipes.

When used in conjunction with a program of regular inspection, cleaning and flushing, it helps to keep piping, wells and basins unobstructed, free-flowing and clear of deposits.

## DIRECTIONS

Use at a rate of 1/2 to 1 gallon per 1000 gallons of flushing water.

## RECOMMENDED DOSAGES PER 400 FEET

4" Line.....	2 to 4 gallons
6" Line.....	4 to 6 gallons
8" Line.....	6 to 8 gallons
10" Line.....	8 to 10 gallons

REMOVES MUD, DIRT AND SILT FROM STORM DRAINS AND SANITARY SEWERS

## CAUTION

Harmful if swallowed. See side panel for further cautions and first aid instructions.

**KEEP OUT OF REACH OF CHILDREN**

## CAUTION

Harmful if swallowed. Avoid prolonged contact with skin. If splashed in eyes, flush with plenty of water for at least 15 minutes. If irritation persists, obtain medical attention. If swallowed, give several glasses of water and call physician immediately.

**KEEP OUT OF REACH OF CHILDREN**

This product contains	CAS Number
Non-ionic polyacrylamide resin	No CAS Number
Water	7732-18-5

38091300

NET CONTENTS:

5    6    20    30    55  
GALLONS

Sold By: