HIGH HEAT Product # 616

Granular drain opener

This drain opener contains powerful caustic granules activated with aluminum needles to quickly unclog drains and sewers and keep them free-flowing. When added to water, it releases large amounts of heat and turbulence to liquefy, dissolve and loosen fats, oils and other organic matter that typically clog drains and sewer lines. Even though it's extremely powerful, it will not harm drains, pipes and septic systems.

Use in:

Manholes Drains Food plants Packing houses Canneries

Effective Against

- Animal fats
- Hair
- Organic matter

- Vegetable oils
- Paper
- Hard-water soap deposits

Features and Benefits

- Contains powerful heat-generating aluminum needles.
- Releases large amounts of heat and turbulence to liquefy blockages in drain and sewers.
- Looses and dissolves greases and other organic material.

Properties	
Appearance	Yellow pellets with aluminum

granules None

None

pH..... 14.0 Stability..... 1 year

Solubility in water..... Complete (very reactive)

Directions Complete directions on product label

Manholes: Pour or shovel 25 pounds into manholes above the clog. Industrial: Use 2-3 pounds in normal drains. Where grease or organic waste is high, use 5-8 pounds.

Authorizations

NSF L1: Compounds for use in sewer or drain.

Active Ingredients Sodium H

Fragrance..... Flash point.....

Sodium Hydroxide
Sodium Nitrate
Sodium Chloride

Aluminum metal

Octyl phenol ethoxylate

CAS Number 1310-73-2

7631-99-4 7647-14-5

7429-90-5

9002-93-1

Safety

Danger: Poison: Harmful or fatal if swallowed. Causes severe burns. Keep out of the reach of children.

DOT Shipping (ground transportation)

Proper Shipping Name: Corrosive solid, basic, inorganic, n.o.s.

(Sodium Hydroxide)

Class: 8

UN3262 ID Number: Packing Group:



Quantities

55 pound pail