

Prevents oxygen pitting in steam boilers

This liquid is a catalyzed oxygen scavenger that quickly removes dissolved oxygen from boiler feedwater. It also provides additional protection against pitting and corrosion of internal boiler surfaces when used in conjunction with scale and corrosion inhibitors. Plus, it can be mixed with other treatment products and fed into the feedwater system, or fed directly into the boiler.

Steam Boiler & Closed Loop Treatment That Is Effective Against

- Corrosion
- Rust

Features and Benefits

- Quickly attacks dissolved oxygen in boiler-feed water before it becomes in contact with metal surfaces.
- Can be safely used in boiler systems with our without a deaerator.
- Is effective in both steam boilers and closed loop recirculating systems.

Properties

Appearance.....	Pink Liquid
Fragrance.....	Sulfur
Concentrate.....	Yes
Specific gravity.....	1.17
Flash point.....	None
pH.....	6.0-7.0

Directions Complete directions on product label

Recommended for use with a continuous feed system to maintain a sulfite level between 20 - 40 ppm.

Active Ingredients

Water	
Sodium Metabisulfite	
Sodium Sulfite	
Cobalt sulfate	

CAS Number


7732-18-5
7681-57-4
7757-83-7
10124-43-3

Safety

Caution: May be harmful if swallowed. Irritant. Keep out of the reach of children.

DOT Shipping (ground transportation)

Proper Shipping Name:	None
Class:	None
ID Number:	None
Packing Group:	None



Quantities

- 30, 35 & 55 gallon
- 5 or 6 gallon
- 6 X 1 gallon
- 4 X 1 gallon